品质改变世界
QUALITY CHANGES THE WORLD

SANY®

三一 C8 全系列摊铺机

SANY C8 WHOLE SERIES OF PAVERS

三一重工股份有限公司
SANY HEAVY INDUSTRY CO., LTD.

中国 湖南 长沙经济技术开发区三一工业城
Address: SANY Industry Town, Changsha National Economic & Technical Development Zone, Hunan, China
邮编 Zip 410100
电话 Tel 0731-84031888　售后服务热线 After-sales service 4008 87 8318
传真 Fax 0731-84031999　咨询投诉电话 Consulting and complaint telephone 4008 87 9318

代理商信息
Agent Information

如产品配置（含技术参数）发生变动，恕不另行通知，以交机实物为准。

版权为三一重工所有，未经三一重工书面许可，本目录任何部分的内容不得被复制或抄袭用于任何目的。

三一重工市场部制作 2019 年 9 月

As technology is being updated unceasingly, technical parameters are subject to change without prior notice. The machine in the picture may include auxiliary equipment. Copyright belongs to Sany Heavy Industry, no part of this catalogue can be reproduced or copied for any purpose without written permission of Sany Heavy Industry.

Produced by Sany Marketing Department May 2019.

www.sany.com.cn

SANY®

三一云二维码

www.sany.com.cn

SANY
品质改变世界

目录 Contents

LEADING BRAND IN CHINA WITH WORLD CLASS QUALITY

国际品质 中国第一

2011 年荣获中国 “摊铺机第一品牌称号”
连续 7 年，全国销量第一

Won "No. 1 Brand for Paver in China" in 2011
Sales ranked No. 1 in China for 7 consecutive years

P03 三一路机 Sany Road Machinery

P05 SSP 系列多功能摊铺机 SSP Series Multifunctional Paver

P11 SAP 系列超级摊铺机 SAP Series Super Paver

P17 精益制造 Lean Manufacturing

P19 品质保证 Quality Assurance

P21 施工案例 Construction Cases

P23 服务承诺 Service Commitment

三一路面机械

三一重工股份有限公司是国内最大规模的路面机械成套设备供应商之一。产品涵盖摊铺机系列、压路机系列、沥青搅拌设备系列、平地机系列、铣刨机系列。

公司秉承“品质改变世界”的历史使命，以“为客户创造最大价值”为己任，设立三一路机美国研究院和三一路机德国研究院，产品融汇全球最尖端科技，其中由美国设计的重型平地机和德国设计的双钢轮压路机，是具有国际一流水平的精品，其摊铺机和沥青搅拌站连续五年蝉联国内销量第一，为中国第一品牌，畅销全球六十余个国家。

面对高速公路、机场和城市高等级路面施工和全球市场，我们为客户提供路面施工成套设备和系列解决方案。打造无以伦比的服务体系，为客户免除后顾之忧，在中质协服务满意度调查中，三一连续三年获得满意度第一，赢得了客户的高度信赖。“筑路中国 · 畅行天下”，三一路机将不遗余力地服务于全球经济发展和道路建设。

SANY ROAD MACHINERY

SANY Heavy Industry Co., Ltd. is one of the largest complete equipment suppliers of road machinery. The products cover pavers, rollers, asphalt batching plants, graders, and milling machines etc.

Taking “Quality changes the world” as the mission and “Creating the greatest values for customers” as the duty, Hunan SANY Road Machinery Co., Ltd., has set up SANY (USA) Road Machinery Institute and SANY (Germany) Road Machinery Institute and integrated the most cutting-edge technologies into its products, of which: heavy graders designed by the United States and double drum vibratory rollers designed by Germany are high-quality products of internationally top level; the pavers and asphalt batching plants, having been best sellers in China for 5 consecutive years, are No.1 brand in China and sold well in over 60 countries across the world.

Faced with the construction of expressways, roads in airports and urban high-class roads and with the global market, we provide road construction complete equipment and series of solutions. We have created an unmatched service system to eliminate the customers’ worries. In the service satisfaction surveys performed by China Association for Quality, SANY has ranked No.1 for 3 consecutive years and won high trust from the customers. Keeping “Construct roads in China, Connect with the world freely” in mind, SANY Road Machinery Co., Ltd. will spare no effort in serving the global economic development and road construction.

SANY
品质改变世界

SSP SERIES MULTIFUNCTIONAL PAVER

SSP 系列多功能摊铺机

大厚度摊铺 唯我独尊

Heavy thickness pavement
No.1 in China.

动力强劲

- 动力充分满足摊铺机各种工况下动力需求。
- 经济档转速下噪音更低，油耗更少，机器可靠性得到大幅提升。

高效

- 任何工况，确保摊铺能力大于 1000t/h，行业内绝无仅有。
- 一次成型厚度达 50 厘米，可实现两层稳定土一次摊铺成型，提升工作效率 50%。
- 快速拼装熨平板，2 人可在 2.5 小时内完成 10 米熨平板拼装。
- 使用自主研发的 SYMC 控制系统，可实现远程技术支持和设备管理。
- 螺旋分料装置实现了一键整体提升，极大提高了设备的操作便捷性和工况适应能力。

经济

- 输料通道采用增厚耐磨钢板制作，耐磨件寿命提升 30%。
- 连续工作能力强，确保 50 度高温环境连续不停机作业要求。

STRONG POWER

- The power can satisfy the paver's demands under different working conditions;
- Low noise, less oil consumption and better machine reliability under economic gear mode.

EFFICIENCY

- It is able to ensure over 1,000 t/h paving capacity under all conditions, which is peerless in the industry.
- With 50cm paving thickness, it can realize the paving and molding of two layers of stable soils in one time, which can improve working efficiency by 50%.
- 2 persons can finish assembling 10 m screed within 2.5 hr.
- Adopt self-developed SYMC control system to achieve remote technical support and equipment management.
- The spiral feed divider can realize one-key overall lifting to improve equipment operation convenience and work adaptability significantly.

ECONOMY

- The conveying channel is made of thickened wearing-resistant steel plate and the service life of wearing-resistant parts is increased by 30%.
- Strong continuous working capacity to ensure the non-stop working requirements under 50°C temperature.

SANY
品质改变世界

TECHNICAL PARAMETER
技术参数

SSP 系列多功能摊铺机技术参数

型号	SSP 系列多功能摊铺机		
	SSP125C-8	SSP90/100C-8	SSP80C-8
发动机型号	三一动力 D07S3	三一动力 D07S3	三一动力 D05S3
发动机额定功率（kW）	180	170	155
发动机额定转速（rpm）	2200	2050	2050
摊铺能力（t/h）	1100	1000	950
最大摊铺厚度（cm）	55	50	50
最大作业速度（m/min）	16	16	23
最大转场速度（km/h）	2.8	2.8	2.5
螺旋叶片 (mm)	(Φ420、Φ360)/280	(Φ420、Φ360)/280	(Φ420、Φ360)/280
料斗容量 (m^3)	8.5	8.5	8.5
熨平板选择	SSP125C-8	SF250（基本宽度 2.5m）	
	SSP100C-8	SF250（基本宽度 2.5m）	
	SSP90C-8	SE570（基本宽度 3-5.7m，机械加宽至 9.2m）	
	SSP80C-8	SE470（基本宽度 2.5-4.7m，机械加宽至 8.2m）或 SE570(基本宽度 3-5.7m，机械加宽至 7.7m)	
		SF250（基本宽度 2.5m）	

Technical Parameters of SSP Series Multifunctional Paver

Model	SSP Series Multifunctional Paver		
	SSP125C-8	SSP90/100C-8	SSP80C-8
Engine Model	SANY D07S3	SANY D07S3	SANY D05S3
Rated Power of Engine (Kw)	180	170	155
Rated Rotating Speed of Engine (rpm)	2200	2050	2050
Paving Capacity (t/h)	1100	1000	950
Max. Paving Thickness (cm)	55	50	50
Max. Paving Speed (m/min)	16	16	23
Max. Travel Speed (Km/h)	2.8	2.8	2.5
Auger blade (mm)	(Φ420、Φ360)/280	(Φ420、Φ360)/280	(Φ420、Φ360)/280
Hopper Capacity (m^3)	8.5	8.5	8.5
Options of Screed	SSP125C-8	SF250（basic width2.5m）	
	SSP100C-8	SF250（basic width2.5m）	
	SSP90C-8	SE570（basic width 3-5.7m，Extensive width 9.2m: mechanical）	
	SSP80C-8	SE470（basic width 2.5-4.7m，Extensive width 8.2m: mechanical）or SE570（basic width3-5.7m，Extensive width 7.7m: mechanical）	
		SF250（basic width2.5m）	





L 配 SF250 熨平板为 6710mm，配 SE570/470 熨平板为 7250mm
6710 mm screed equipped with SF250, and 7,250 mm screed equipped with SE570/470

TECHNICAL PARAMETER
技术参数

SSP 系列多功能摊铺机基本配置及选配表

型号	所属部分	选项	标配	选配
	主机	找平仪	三一	MOBA
		其它	/	高原附件
SSP125C-8	SF250 拼装熨平板	熨平板长度	12.5m	10m
				9m
				8m
				6m
				2.5m
		加热方式	气加热	/
		振动机构	有	/
SSP100C-8	SF250 拼装熨平板	熨平板长度	10m	9m
				8m
				6m
				2.5m
		加热方式	气加热	/
		振动机构	无	有
SSP90C-8	SE570 伸缩熨平板	熨平板长度	9.2m	7.7m
				7m
				7.2m
		加热方式	电加热	/
		振动机构	有	/
SSP80C-8	SE470 伸缩熨平板	熨平板长度	8.2m	6.7m
				6.2m
				4.7m
		加热方式	电加热	/
		振动机构	无	有
	SF250 拼装熨平板	熨平板长度	8m	6m
				2.5m
		加热方式	气加热	/
		振动机构	无	有
	SE570 伸缩熨平板	熨平板长度	7.7m	7.2m
				5.7m
		加热方式	电加热	/
		振动机构	无	有

Basic and Optional Configuration of SSP Series Multifunctional Paver

Model	Part	Option	Standard Configuration	Optional
	Main machine	Levelling System	SANY (Control+Sensor)	MOBA
		Miscellaneous	/	High altitude accessories
SSP125C-8	SF250 splicing screed	Screed length	12.5m	10m
				9m
				8m
				6m
				2.5m
		Heating Mode	Gas Heated	/
		Vibration Mechanism	Yes	/
SSP100C-8	SF250 splicing screed	Screed length	10m	9m
				8m
				6m
				2.5m
		Heating Mode	Gas Heated	/
		Vibration Mechanism	NO	Yes
SSP90C-8	SE570 expansion screed	Screed length	9.2m	7.7m
				7.2m
				5.7m
		Heating Mode	Electric Heated	/
		Vibration Mechanism	Yes	/
SSP80C-8	SE470 expansion screed	Screed length	8.2m	6.7m
				6.2m
				4.7m
		Heating Mode	Electric Heated	/
		Vibration Mechanism	NO	YES
	SF250 splicing screed	Screed length	8m	6m
				2.5m
		Heating Mode	Gas Heated	/
		Vibration Mechanism	NO	Yes
	SE570 expansion screed	Screed length	7.7m	7.2m
				5.7m
		Heating Mode	Electric Heated	/
		Vibration Mechanism	NO	Yes

SAP SERIES SUPER PAVER
SAP 系列超级摊铺机

稳定可靠

- 电气汽车化线束——杜绝接线松动、接触不良。杜绝线路故障。
- 高效散热模型——机舱内部采用分舱导流技术，优化热量传递路线，提升散热能力，实现高温环境连续施工不停机。

领先技术带来摊铺效果好

- 高强熨平板——业内最强刚性设计，采用框架结构及双层防扭梁设计，施工更平整、更稳定。
- 输分料防离析技术——全比例输分料控制，匹配泵－马达模糊控制，大直径、大节距螺旋叶片提升搅拌均匀度，低匀速供料技术保证输料平稳性，提升路面平整度。
- 远程程序升级——提供最及时技术更新及服务。

STABLE AND RELIABLE

- Electrical motorization hardness- eliminating loose wire and poor contact. Eliminating line faults.
- Highly efficient heat dissipation model-compartment heat division technique is used inside the compartment to optimize heat transfer line, improve heat dissipation capacity and ensure non-stop working under a high temperature environment.

Advanced technique contributes to excellent paving effect

- Superior screed- the most rigid design in the industry; framework structure and dual-layer anti-beam torsion design are used to ensure more smooth and stable construction.
- Material conveying and distribution anti-separation technology-Full proportion material conveying and distribution control is matched with pump- motor fuzzy control; large diameter and pitch spiral impeller improves the mixing evenness; the low and constant speed supply technique satisfies the conveying stability and improves the pavement evenness.
- Remote program upgrading---providing timely technical upgrading and support.

TECHNICAL PARAMETER
技术参数

SAP 系列超级摊铺机技术参数

型号	SAP120C-8	SAP100C-8	SAP90C-8	SAP60C-8	SAP45TC-8
发动机型号	三一动力 D07S3	三一动力 D07S3	三一动力 D07S3	康明斯 QSB4.5	潍柴 WP4
发动机额定功率（kW）	170	170	170	97	92
发动机额定转速（rpm）	1900	2050	2050	2000	1900
摊铺能力（t/h）	1100	900	900	450	250
最大摊铺厚度（cm）	35	35	35	25	25
最大作业速度（m/min）	24	16	16	20	20
最大转场速度（km/h）	5.0	2.8	2.8	2.5	2.0
螺旋叶片（mm）	（Φ480、Φ400)/350	（Φ480、Φ400)/350	（Φ480、Φ400)/350	Φ360/280	Φ300
料斗容量（m^3）	8.5	8.5	8.5	6	6
熨平板选择	SF250	SF250	SE570	SE370	SE450

Technical Parameters of SAP Series Super Paver

Model	SAP120C-8	SAP100C-8	SAP90C-8	SAP60C-8	SAP45TC-8
Engine Model	SANY D07S3	SANY D07S3	SANY D07S3	CUMMINS QSB4.5	WEICHAI WP4
Rated Power of Engine (Kw)	170	170	170	97	92
Rated Rotating Speed of Engine (rpm)	1900	2050	2050	2000	1900
Paving Capacity (t/h)	1100	900	1100	450	250
Max. Paving Thickness (cm)	35	35	35	25	25
Max. Paving Speed (m/min)	24	16	24	20	20
Max. Travel Speed (Km/h)	5.0	2.8	5.0	2.5	2.0
Auger blade (mm)	（Φ480、Φ400)/350	（Φ480、Φ400)/350	（Φ480、Φ400)/350	Φ360/280	Φ300
Hopper Capacity (m^3)	8.5	8.5	8.5	6	6
Option of Screed	SF250	SF250	SE570	SE370	SE450

尺寸 Size	SAP120C-8	SAP100C-8	SAP90C-8	SAP60C-8	SAP45TC-8
A(mm)	3890	3890	3890	3760	3767
C(mm)	3278	3278	3278	2570	2787
D（°）	13	13	13	12	24
F(mm)	2700	2700	2700	2100	1800
G(mm)	2022	2022	2022	1505	1457
H(mm)	3470	3470	3470	3265	3047
L(mm)	6790	6790	7250	6500	6618





SANY
品质改变世界

TECHNICAL PARAMETER
技术参数

SAP 系列超级摊铺机基本配置及选配表

型号	所属部分	选项	标配	选配
SAP120C-8	主机	清洗装置	电动清洗	/
		找平仪 + 平衡梁	SAP120C-8(MOBA) 其余（三一）	三一
		其它	/	高原附件
	SF250 拼装熨平板	熨平板长度	12m	11m
				10m
				9m
				8m
				6m
				2.5m
		加热方式	电加热	气加热
		振动机构	有	/
SAP100C-8	SF250 拼装熨平板	熨平板长度	10m	9m
				8m
				6m
				2.5m
		加热方式	电加热	气加热
		振动机构	有	/
SAP90C-8	SE570 伸缩熨平板	熨平板长度	9.2m	7.7m
				7.2m
				5.7m
		加热方式	电加热	/
		振动机构	有	/
型号	所属部分	选项	标配	选配
SAP60C-8	主机	清洗装置	电动清洗	/
		找平仪	三一	MOBA
		其它	/	高原附件
	SE370 伸缩熨平板	熨平板长度	6m	5.2m
				4.5m
				2m
		加热方式	电加热	气加热
		振动机构	有	/
SAP45TC-8	SE450 伸缩熨平板	熨平板长度	4.5m	/
		加热方式	电加热	气加热
		振动机构	无	有

Basic and Optional Configuration of SAP Series Super Paver

Model	Part	Option	Standard Configuration	Optional
SAP120C-8	Main machine	Cleaning device	Electric	/
		Leveling instrument+balance beam	SAP120C-8(MOBA)Other（SANY）	SANY
		Others	/	High altitude accessories
	SF250 splicing screed	Screed length	12m	11m
				10m
				9m
				8m
				6m
				2.5m
		Heating method	Electric heating	Gas heating
		Vibration mechanism	Yes	/
SAP100C-8	SF250 splicing screed	Screed length	10m	9m
				8m
				6m
				2.5m
		Heating method	Electric heating	Gas heating
		Vibration mechanism	Yes	/
SAP90C-8	SE570 expansion screed	Screed length	9.2m	7.7m
				7.2m
				5.7m
		Heating method	Electric heating	/
		Vibration mechanism	Yes	/
Model	Part	Option	Standard Configuration	Optional
SAP60C-8	Main machine	Leveling instrument+balance beam	Electric	/
		Levelling system	SANY	MOBA
		Others	/	High altitude accessories
	SE370 expansion screed	Screed length	6m	5.2m
				4.5m
				2m
		Heating method	Electric heating	Gas heating
		Vibration mechanism	YES	/
SAP45TC-8	SE450 expansion screed	Screed length	4.5	/
		Heating method	Electric heating	Gas heating
		Vibration mechanism	NO	YES

LEAN MANUFACTURING
精益制造

路机人挥洒汗水，精益求精
不断刷新中国制造的更高水平
更多的“第一”背后
是路机人改写中国制造至中国创造的实干之心

Personnel in the Company make every efforts to constantly strive for perfection and continuously achieve a higher Chinese manufacturing level;
Behind various reputable “No.1” achievements is their ambition to realize Chinese creation from Chinese manufacturing.

● 进口机床加工生产线
Imported Machining Production Line

● 进口卧式加工中心柔性线
Flexible line of imported horizontal machining center

● 专业的库存管理和防损措施
Professional Inventory Management and Damage-Prevention Measures

● 无尘恒温的精密传动车间
Dust-free Constant Temperature Precision Transmission Workshop

精心设计、优化布局、技术革新、注重品控，实现路机产品全面流水化制造
生产管理信息化（MES 系统）、全自动焊接机器人、AGV 小车、自动化立体仓库……
不断开展自动化、智能化的创新研究，“新工艺、新设备、新材料”的广泛应用，极尽苛刻的质量品控，使得每一件路机产品至臻完美，面对各种复杂作业环境尽显卓越性能

三一人执着地闯出一条崭新的科技发展之路，为中国工程机械行业树立了全新的标杆

With meticulous design, optimal layout, technical innovation and emphasis on quality, the product can realize the full automatic manufacturing process of road machinery.
Production management information (MES system), full automatic welding robot, AGV trolley and automatic 3D warehouse...
With a strong focus on the innovation research of automation and intelligence constantly, the Company has applied “new technology, new equipment and new materials” widely and is always strictly on product quality to make all the road machine products perfect. The machines can show their superior performance under all different complicated operating environments.

All the staffs in Sany are brave to make scientific development, setting a typical example for Chinese engineering machinery industry.

QUALITY ASSURANCE
品质保证

● 爬坡性能及驶入角
Gradeability and Approach Angle

● 密实度仪
Compactness Meter

● 红外热成像仪
Infrared Thermal Imager

● 平整度仪
Profilometer

● 熨平板试验
Screed Test

● 表面构造深度测试
Depth Measurement of Surface Texture



研发试验体系

为打造一个国际领先的路面机械研发平台，三一路机依托工程 机械远程监控服务与故障诊断实验室、液压实验室、机电液控与仿真实验室、柴油机实验室、设备疲劳（寿命）实验室、焊接实验室、强度（应力）实验室、耐磨材料实验室、汽车底 盘全自动检测线等 9 大试验检测中心及 58 个企业级实验室， 形成跨体系跨部门产品开发流程；

通过“试验基础设施、新产品开发试验、客户体验平台、工况 模拟数据库”建设，建立了整车试验、零部件试验和仿真试验 三级试验体系，目前已具备沥青站、摊铺机、平地机、压路机、 铣刨机的开发及相关核心技术的研究、试验能力，全面提升研发核心竞争力。

R&D and Test System

In order to create a world leading R & D platform for road machinery, Sany Road Machinery Co., Ltd. has formed a multi-system-and-department product development process in virtue of its 9 test and inspection centers such as remote monitoring service and fault diagnosis lab for engineering machinery, hydraulic lab, electromechanical hydraulic control and simulation lab, diesel lab, equipment fatigue (service life) lab, welding lab, strength (stress) lab, wearing resistant materials lab, auto chassis full automatic detection line and 58 enterprise labs.

By constructing “test infrastructure, new product development test, customer experience platform and working condition simulation database”, Sany has established a 3-level system including whole vehicle test, parts test and simulation test; it has owned the development and relevant core technology research and test capacity of asphalt batching plant, paver, grader, road roller and milling machine.

CONSTRUCTION CASES
施工案例

湄潭高速公路建设

思遵高速公路起于思南县鹦鹉溪镇双龙村，经过铜仁地区思南县、德江县和遵义市凤冈县、湄潭县、遵义县、红花岗区止于遵义县龙坑镇，与杭瑞高速公路遵毕段相接，是贵州省高速公路网规划的重要组成部分。

施工设备：一台 SAP240C-5 高等级沥青摊铺机

工程特点：该高速公路段长 20 公里，双向四车道，3 个月的施工时间，要对本公路进行中层和面层两层摊铺。

CONSTRUCTION OF MEITAN EXPRESSWAY
By starting from Shuanglong Village, Yingwuxi Town, Sinan County, Sinan-Zunyi Expressway runs through Sinan County and Dejiang Town, Tongren District, and Fenggang Town, Meitan County, Zunyi County and Honghuagang District, Zunyi City and ends at Longkeng Town, Zunyi County. It connects Bijie Section, Hangzhou-Ruili Expressway. It serves a critical part in Guizhou's expressway network planning.
Construction equipment: One set of SAP240C-5 high-grade asphalt paver
Construction features: This expressway is 20 km long with 4 lanes on each side. Construction period is 3 month. Middle layer and surface need to be paved.

遂资高速公路建设

遂资高速承建方在对比国内外众多筑路品牌，了解并查看施工现场和摊铺效果后，决定采用三一的高等级摊铺机 SAP240C-5 进行施工，打破了国内品牌上不了高速的“魔咒”。施工期间三一 SAP240C-5 凭借着优越的作业性能，高密实度，高平整度的摊铺效果，获得了各方的交口称赞。2012 年 8 月 3 日，路面研究院专业人员对摊铺路面进行检测，其摊铺的各项指标均达到高速路面专业标准。

CONSTRUCTION OF SUINING-ZIYANG EXPRESSWAY
After comparing a number of foreign and domestic road building brands and understanding and investigating the construction site and paving effect, Suining-Ziyang Expressway contractor finally decided to use Sany high-grade paver SAP240C-5, which makes the history that domestic brand pavers cannot be used for expressway construction. During the construction period, Sany SAP240C-5 was praised highly by all parties thanks to its superior performance, and high density and high evenness paving effect. On August 3, 2012, the technicians from pavement research institute confirmed all pavement indexes reached the professional requirements for expressway pavement after detecting the pavement.

山东滕州城市道路施工

2017 年 7 月，山东滕州城市主干道施工，摊铺机 12 米宽，5cm 厚，摊铺速度 7.5m/min 左右，摊铺平整度高，表面质量高，得到客户和当地交通局领导的高度赞赏。

CONSTRUCTION OF URBAN ROAD OF TENGZHOU, SHANDONG
The main urban road of Tengzhou, Shandong was constructed in July 2017. The paver is 12 m in width and 5 cm in thickness with the pavement speed of about 7.5 m/min. The high pavement evenness and surface quality won the praise of the client and local leaders from transportation bureau.

SANY
品质改变世界

三一路机“123”价值服务承诺

Road Machinery Product "123" Value Service Commitment

1送 SANY

购买三一路机设备免费赠送人工服务费

◆ 路机产品按《操作保养手册》保养节点且使用三一纯正配件，免收人工服务费。

2保 SANY

黑色路面产品关重部件保修期为 2 年或 2000 小时（先到为准）

◆ 产品范围：摊铺机、双钢轮压路机、轮胎压路机、沥青搅拌站。

3补 SANY

补偿一

◆ 产品质量问题引起停机故障 48 小时内未修复，优先提供备用机、无法提供备用机的按标准补偿；

补偿二

◆ 购买常用件 24 小时内未发货按标准补偿；

补偿三

◆ 压路机、平地机常用件高于市场价、按差价的 2 倍补偿。

以上条款的最终解释权归三一重工所有

售后服务热线
After-sale services hotline
4008 87 8318

咨询投诉电话
Consulting and complaint telephone
4008 87 9318

Clients who purchased SANY Road Machinery Equipments will be free of labor service fee

◆ Road machinery products shall be free of labor maintenance fee in accordance with the requirements of the Operation and Maintenance Manual for maintenance time nodes and using SANY certified accessories.

The warranty period for key parts of black Road Machinery Product is 2 years or 2,000 hours (whichever ends first)

◆ Product scope: Paver, Double Steel Roller, Tyre Roller, Asphalt Batching Plant.

Compensation I

◆ If the machine failure caused by product quality problems has not been repaired within 48 hours, clients should be provided the standby machine priority, and the situation where the standby machine cannot be used should be compensated according to the compensation standard.

Compensation II

◆ Clients will be compensated for non-delivery of common parts within 24 hours after purchase according to the compensation standard;

Compensation III

◆ If the price of common parts of Road Roller and Grader is higher than market price, clients will be compensated by 2 times the price difference.

The final interpretation of the above terms is owned by SANY Heavy Industry

久隆筑路机械保险
提供更贴心的服务

沥青搅拌站
财产保险

筑路机械
设备第三者
责任保险

雇主责任
保险

筑路机械
设备财产
一切保险

高性价比 价格更厚道，责任更宽泛

理赔快捷 领先行业水平，赔付更快捷

全面保障 产品创新，专业打造

久隆保险
LONG Insurance

基于装备制造业的专业财险公司