



# 三一预制件专用运输车

PRECAST CONCRETE TRANSPORT SEMI-TRAILER

## 高回报 High Return

利润一台顶十台

Ten times earnings

半年可回本

The cost can be recovered in half a year

减少吊装设备投入

Reduce purchase of cranes

## 高效率 High Efficiency

装卸不求人

loading and unloading Without cranes

快速固定

Rapid Fixation

省时省力省人员

The time and labor can be saved

## 高机动 High Mobility

越野模式适合乡村、山路、隧道、桥梁复杂路况

Cross-country mode is suitable for complex road ,such as conditions of countryside, mountain roads, tunnels and bridges

长短款可选

There are long models and short models for option

根据路况随时调整车体高度

The height of the vehicle can be adjust according to the road conditions at any time

## 安全可靠 Safe and reliable

低重心，左右桥平衡防倾翻

Low gravity, left and right bridges are auto balanced to prevent tilting

自适应减震，配备ABS系统

Adaptive Damping, Equipped with ABS System

箱体全方位防护，构件损伤少

The box is fully protected and the PC are less damaged.



经测算：普通平板车2台一年获利30万元，  
预制件运输车1台一年获利166万元，  
超过5倍的利润！

扫一扫关注三一预制件专用运输车

产品型号 Model	SY9401TYC (标准款)	SY9402TYC (短轴款)
半挂车总质量 Perm. Gross vehicle weight	40000 kg	40000 kg
半挂车整备质量 Weight approx	10500 kg	9000kg
有效载荷 Payload when loaded irregularly approx	29500 kg	31000kg
鞍座载重 Perm. Fifth wheel load approx	16000 kg	16000 kg
牵引销型号 Towing pin model	90#	90#
外形尺寸长/宽/高 Outer L/W/ H m	12310/2550/ 3260 mm	9800/2550/3260mm
装货区长/宽 Loading length/width	9000/1530 mm	6500/1530mm
牵引销离地高度 Fifth wheel height	1260-1360 mm	1260-1360 mm
轮胎规格 Tyre Spec	Φ385/65 R22.5	Φ385/65 R22.5
夹具数量 Fixing deviceQty.	标配2对	标配2对
定制托盘数量 (长宽高 L/W/ H 9.5×1.5×3 m) Custom tray Qty.	数量按照客户要求定制	数量按照客户要求定制

